ecosoft

STANDARD PRO REVERSE OSMOSIS FILTER WITH MINERALIZATION





KEY FEATURES

- Reliable and affordable solution
- 5 stages of water purification including mineralization
- Certified by the Water Quality Association (WQA) to meet NSF/ANSI 58:2022, NSF/ANSI/CAN 372:2020, and CSA B483.1:2017 standards, ensuring superior quality and safety

FILTRATION TECHNOLOGY:

- 5 micron PP sediment filter
- GAC coconut shell carbon filter
- 1 micron sediment PP filter
- 50 GPD RO membrane element
- Mineralizing postfilter

SPECIFICATION:

Code	Flow capacity, LPD (GPD)	Inlet pressure, bar (psi)	Connections	Total volume of storage tank, L (gal)	Dimensions, H x W x D, mm (in)
MO550MECOSTD	190 (50)	3-6 (43.5-87)	1/2", 3/8"	12 (3.2)	414 × 422 × 135 (16.5 × 16.1 × 5.9)

COMPONENTS:

- Filter housing
- · Ecosoft pack of pre-filters for reverse osmosis filter
- Membrane element 50 GPD (190 LPD)
- Ecosoft mineralizing postfilter
- · Chrome ball valve faucet for purified water

- Plastic pressure tank (total vol. 12 L/3.2 gal, usable vol. up to 7 L/1.8 gal) and tank valve
- Feed water adapter, feed valve, drain saddle
- Pack of color tubes (4 pcs.) for convenient filter installation
- Service wrench
- User manual

Unit weight (net/gross), kg: 8.08/9.12 lb: 17.64/19.84 Box dimensions, m: 0.51 × 0.52 × 0.27 in: 20.1 × 20.5 × 10.6

ECOSOFT STANDARD PRO REVERSE OSMOSIS FILTER WITH MINERALIZATION

Code	Product	Pieces in box	Boxes on pallet	Pieces on pallet
MO550MECOSTD	Standard PRO reverse osmosis filter with mineralization	1	24	24