

# ECOSOFT ROBUST 1500 REVERSE OSMOSIS FILTER

**APPLICATION:** Cafes, hotels, offices, schools, laboratories, dental offices, private homes, etc.



## KEY FEATURES

- Flow rate 100 liters per hour
- Made to run 20 hours per hour
- Recovery rate 60-65% - filter is economical and environmentally-friendly
- Built-in pressure gauges indicating pump conditions
- CE marked and confirmed to be safe by EC New Approach Directives

## SPECIFICATION

Code	Flow capacity <sup>1</sup> , LPH (GPH)	Water consumption, LPH (GPH)	Power supply	Power consumption, kW (hp)	Dimensions, H x W x D, mm (in)
<b>ROBUST1500ECO</b>	90-100 (24-26.5)	140-165 (37-43)	180-240 V, 50-60 Hz	0.12 0.16	417 x 367 x 297 (16.4 x 14.4 x 11.7)

<sup>1</sup>At 25 °C feed water temperature, TDS 1000 ppm

## SYSTEM COMPONENTS:

- Assembled filter
- Pre-filter and post-filter
- Reverse osmosis membranes
- Drain saddle
- Installation fitting set
- Set of tubes
- Service wrenches

## FILTRATION STAGES:

- 5 micron PP sediment filter 2.5"×10"
- GAC coconut shell carbon filter 2.5"×10"
- Ecosoft membrane element (1 pc.) 3.0"×12"
- CTO carbon post-filter 2.5"×10"

## ECOSOFT ROBUST 1500 REVERSE OSMOSIS FILTER

Code	Product	Membrane	Pieces on pallet
<b>ROBUST1500ECO</b>	Direct flow RO Ecosoft ROBust 1500	1 x CSV3012500ECO	16

## ROBUST 1500 REPLACEMENT FILTERS

Code	Description	Replacement/ months	Quantity, pcs
<b>CHV3ECO</b>	Ecosoft advanced pack of replacement filters 1-2-3	3	1
<b>CSV3012500ECO</b>	Ecosoft 500 GPD membrane element	12	1