

ECOSOFT ROBUST 3000 MAX REVERSE OSMOSIS FILTER

APPLICATION: Restaurants, water production facilities, small breweries, car washes, and private homes, among others.



KEY FEATURES

- Flow rate 150 liters per hour
- Made to run 20 hours per day
- Recovery rate 60% – filter is economical and environmentally-friendly
- Equipped with advanced pre-filtration to treat challenging waters
- Built-in pressure gauges indicating pump conditions
- CE marked and confirmed to be safe by EC New Approach Directives

SPECIFICATION

Code	Flow capacity ¹ , LPH (GPH)	Water consumption, LPH (GPH)	Power supply	Power consumption, kW (hp)	Dimensions, H x W x D, mm (in)
ROBUST3000MAX	150-160 (39-42)	250-300 (66-79)	180-240 V, 50-60 Hz	0.12 0.16	466 x 523 x 406 (18.3 x 20.6 x 16)

¹At 25 °C feed water temperature, TDS 1000 ppm

SYSTEM COMPONENTS:

- Assembled filter
- Pre-filters
- Reverse osmosis membranes
- Drain saddle
- Installation fitting set
- Set of tubes
- Service wrenches

FILTRATION STAGES:

- GAC coconut shell carbon filter BB10
- Carbon block cartridge BB10
- Ecosoft membrane elements (2 pcs.) 3.0"x12"

ECOSOFT ROBUST MINI REVERSE OSMOSIS FILTER

Code	Product	Membrane	Pieces on pallet
ROBUST3000MAX	Direct flow RO Ecosoft ROBust 3000MAX	2 x CSV3012500ECO	8

ROBUST MINI REPLACEMENT FILTERS

Code	Description	Replacement/ months	Quantity, pcs
CHV4510ECO	Ecosoft granular activated carbon replacement filter 4.5"x10"	3	1
CHVCB4510ECO	Ecosoft carbon block cartridge BB10 4.5"x10"	3	1
CSV3012500ECO	Ecosoft 500 GPD membrane element	12	2