

WATER DISPENSER AQA DRINK 20 U

AMBIENT, COLD OR SPARKLING WATER IN SPACE- SAVING VERSION

AQA drink 20 U is the undercounter water dispenser, for those with space problems in the kitchen.

It can be connected to a variety of water filtration systems, which is connected to tap water and provides a great-tasting water – ambient, cold or sparkling. AQA drink 20 U is available with 2 taps (to be purchased separately): a 5-way tap or a dedicated to the water dispenser (to be added to the tap already installed in the kitchen).

The special feature is its open condenser coil, located at the back, which allows for greater and easier heat exchange and thus the cooling of the cooler: small size but great cooling power due to its excellent design.

Electronical (black) + 5-way or 3-way dedicated tap with electrical connection for AQA drink 20



KEY FEATURES

- Ideal for home, office and workplace
- Ambient, cold and sparkling water
- Capacity: 20 l/h
- Undercounter unit



2* DIFFERENT TYPES OF WATER



FOR LARGE DEMAND OF WATER



MINERALIZED WATER



HYGIENIC AND SAFE MATERIAL



STOP TO SINGLE-USE PLASTIC

DESIGN

The BWT AQA drink 20 U dispensers are characterised by a modern design: the white surfaces perfectly complement the silvercoloured ones, giving the dispenser an attractive look that fits into any kitchen or office. Thanks to their compact design they are easy and versatile to position.

TECHNICAL FEATURES

The AQA drink 20 U is small but powerful, efficient and reliable:

the functionality is intuitive and three different types of water are dispensed via its tap*. An open condenser coil is located at the back, which allows for greater and easier heat exchange and thus the cooling of the cooler. The cooling capacity is up to 20 l/h, perfect for offices and also for the home.

INSTALLATION

The installation is very easy – all that is needed is a connection to the water and electricity supply using the supplied kit. No connection to the drain is required. It requires the installation of an any filters (available in two versions*: 5-way or dedicated for the AQA drink 20 U).

TECHNICAL SPECIFICATION

Parameter	
Item n° – WD electrical version	125592401
Item n° – 5-way tap	125592403
Item n° – 3-way dedicated tap	125592404
C – Cold	✓
A – Ambient	✓
S – Sparkling	✓
H – Hot	-
Cooling capacity l/h ($\Delta t = 10^{\circ}\text{C}$)	20
Number of people (approx.)	5 / 20
Cooling technology	Dry evaporator
Cooling control	+4 °C to +12 °C Thermostat
Recirculation pump/stirrer	-
Compressor power, W	150
Refrigerant	R600
Carbonator capacity, l	2.5
Power supply	230 V / 50–60 Hz
Maximum power consumption, W	230
Pump type	Booster pump
Ø water inlet pipe, Inches	1/4"
Ø CO ₂ inlet pipe, Inches	1/4"
Maximum CO ₂ inlet pressure, bar	4.5
Water inlet pressure (min./max.), bar	1.5 / 3.5
Dimensions WD (WxDxH), mm	230 × 360 × 390
Weight kg (approx.)	18
Material of construction	Plastic
Water selection point	5-way or dedicated tap