

COMMERCIAL WATER DISPENSER

AQA DRINK EDGE

The BWT AQA drink EDGE 45 is a tabletop water dispenser characterised by elegant lines and high-quality materials that make it ideal for areas where design is important. The AQA drink EDGE 45 is designed and manufactured in Italy by BWT using only the highest quality materials and technology. The dispenser is robust, reliable over time and meets the highest standards in terms of performance, reliability and product quality.



KEY FEATURES

- Cooling system with ice bank
- Modern and elegant design
- High-quality materials, hygienic and easy to sanitise

AVAILABLE IN WHITE

- Ideal for bars, restaurants and other areas where high performance is required
- 2 types of water: cold and sparkling
- Capacity: up to 45 l/h

All the models can dispense 2 types of water, fresh and fresh sparkling water (the AQA drink EDGE 30 model can also dispense room temperature water).

They are also available in versions with a pre-set dosage: once the amount of water is set (for example that of a pitcher) it will be enough to simply press the button.



2* DIFFERENT
TYPES OF
WATER



FOR LARGE
DEMAND OF
WATER



ICE
BANK
SYSTEM



HYGIENIC
AND SAFE
MATERIAL



STOP TO
SINGLE-USE
PLASTIC



DESIGN

BWT AQA drink EDGE water dispenser is characterised by a modern, compact and functional design.

The glossy surfaces of the front part integrate perfectly with the satin-finish steel ones of the frame, giving the water dispenser an elegant and captivating design, easily adaptable to any environment: restaurant, office or waiting room. Thanks to their compact design, they are easy and versatile to place on the counter and are also available with a matching cabinet.

TECHNICAL FEATURES

Thanks to the water-cooling system with ice bank, the microchannel condenser and the technopolymer pump, AQA drink EDGE stands out thanks to its high performance and reliability, which allows fresh and sparkling water in large quantities, with low power consumption.

The stainless still carbonator and the double cooling coil ensure high and continuous performance over time.

INSTALLATION

Installation is very simple: you only need to connect to the water and electricity supply and connect the CO₂ cylinder.

No drain connection is required as this model is equipped with a drain tray.

TECHNICAL SPECIFICATION

Parameter	
Item No. - White (pre-set dosage)	6193WH/E45TP
Item No. - White cabinet	76193WH/E45MO
Type of installation	Over counter
Cooling capacity, l/h	45
Number of people (approx.)	25 / 50
Water tank capacity, l	6
Cooling control	Thermostat -2 °C to +7 °C
Recirculation pump/stirrer	Recirculation HC/2
Compressor power Hp	1 / 6
Refrigerant	R 290
Carbonator capacity, l	0.6
Power supply	230 V - 50 / 60 HZ
Maximum power consumption, W	370
Pump type	200 l / h technopolymer paddles
Water pump motor, W	120
Ø water inlet pipe, mm	8
Ø CO ₂ inlet pipe, mm	6
Maximum CO ₂ inlet pressure	4.5 max (recommended 3.3 bar)
Water inlet pressure (min./max.)	1.5 min / 3.5 max
Dimensions (W x D x H), mm	290 x 515 x 440
Dispensing area (H), mm	285
Weight kg (approx.)	23
Water selection point	Stainless steel illuminated buttons

The cooling capacity is calculated with Δt= 10°C